


AVENUE 100® PERMEABLE PAVER

REGULAR OR PREMIUM FINISHES



AVENUE 100® PERMEABLE PAVER




	HEIGHT X WIDTH X LENGTH CM / IN	
	10 x 15 x 30	3 ^{15/16} x 5 ^{7/8} x 11 ^{13/16}
	8 mm joint 8% opening area	
Units/Surface	22,2 /m ²	2,06 /ft ²
Qty/row	0,93 m ²	11,63 ft ²
Qty/cube	7,56 m ²	81,38 ft ² 7 rows
Weight/unit	9,9 kg	21,8 lb
Weight/cube	1780 kg	3915 lb



COLORS

-  Granite gray 
-  Light gray 
-  Silver gray
-  Smoke gray
-  Anthracite
-  Opal white 
-  Ivory 
-  Light beige 
-  Sahara beige 
-  Burned beige
-  Sandhill beige
-  Salmon
-  Clay red
-  Red
-  Burgundy
-  Caledonia pink
-  Brown
-  Bistre

FINISHES

- Smooth Regular
- Grenart Regular
- Ground Regular
- Smooth Premium 
- Grenart Premium 
- Ground Premium 

COLORS




Colors with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.

AVENUE 100® PERMEABLE PAVER

REGULAR OR PREMIUM FINISHES

PATTERN



Runner pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Avenue 100 Permeable paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC autoblocking Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, color and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

- 1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.
- 2 Avenue 100 Permeable paver supplied by BOLDUC.
 - 1 Thickness: 10 cm (3^{55/64} in)
 - 2 Nominal Dimensions:
 - 3 Color:
 - 4 Texture (Smooth Regular or Premium, Grenart Regular or Premium ou Ground Regular or Premium Finishes):

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.