

CITADIN® 60 CLASSIC PAVER

REGULAR FINISH



CITADIN 60® CLASSIC PAVER



	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
	6 x 10 x 20	2 ^{3/8} x 3 ^{15/16} x 7 ^{7/8}
Units/Surface	50 / m ²	4,7 / ft ²
Qty/row	0,96 m ²	10,3 ft ²
Qty/cube	11,53 m ²	124,1 ft ² 12 rows
Weight/unit avg.	2,9 kg	6,4 lb
Weight/cube	1610 kg	3540 lb

SPECIFICATIONS	CODES	COLORS
	PPR-880R-10	Gray
	PPR-880R-51	Black

Approximate coverage areas for one bag of polymeric sand (22,7 kg)

6,43 m²

69,2 ft²

COLORS




● Gray




● Black


PATTERNS



Pattern 1
Herringbone pattern



Pattern 2
Runner pattern



Pattern 4
Basket weave pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Citadin 60 Classic Paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.