

CITADIN™ 60 SLAB

REGULAR OR SMOOTH PREMIUM ① FINISHES




① CITADIN™ 60 SLAB - 400 x 600

	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
	6 x 40 x 60	2 ^{3/8} x 15 ^{3/4} x 23 ^{5/8}
Unit/Surface	4,17 / m ²	0,39 / ft ²
Qty/row	0,96 m ²	10,33 ft ²
Qty/cube	10,56 m ²	113,63 ft ² 11 rows
Weight/unit	37 kg	81 lb
Weight/cube	1591 kg	3508 lb

Specifications	Codes	Standard Colors
Regular finish	PTR-446R-15	Gray and charcoal
		Deluxe Colors
	PTR-446R-02	Ice gray
	PTR-446R-21	Ivory beige
	PTR-446R-24	Travertine beige

Approximate coverage areas for one bag of polymeric sand (22,7 kg)

17,65 m² 190,0 ft²



① CITADIN™ 60 SLAB - 600 x 600

	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
	6 x 60 x 60	2 ^{3/8} x 23 ^{5/8} x 23 ^{5/8}
Unit/Surface	2,78 / m ²	0,26 / ft ²
Qty/row	0,72 m ²	7,75 ft ²
Qty/cube	7,92 m ²	85,25 ft ² 11 rows
Weight/unit	56 kg	123 lb
Weight/cube	1200 kg	2646 lb

Specifications	Codes	Standard Colors
Regular finish	PTR-466R-15	Gray and charcoal
		Deluxe Colors
	PTR-466R-02	Ice gray
	PTR-466R-21	Ivory beige
	PTR-466R-24	Travertine beige

Approximate coverage areas for one bag of polymeric sand (22,7 kg)

22,06 m² 237,5 ft²

COLORS



● Gray and charcoal



● Ice gray




● Ivory beige ①




● Travertine beige


PATTERNS



Pattern 1
Checker pattern
(60 x 600 x 600)



Pattern 2
Runner pattern
(60 x 400 x 600)



Pattern 3
Runner pattern
(60 x 600 x 600)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

CITADIN™ 60 SLAB

REGULAR FINISH

TECHNICAL INFORMATION

Product	Standard	Flexural (transverse) strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Citadin 60 slab	CSA A2311	5 MPa (725 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	6 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.