


CITADIN® M60 SLAB

REGULAR OR SMOOTH PREMIUM ① FINISHES



CITADIN® M60 SLAB



	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
A	6 x 16,3 x 32,5	2 ³ / ₈ x 6 ³ / ₈ x 12 ¹³ / ₁₆
B	6 x 32,5 x 32,5	2 ³ / ₈ x 12 ¹³ / ₁₆ x 12 ¹³ / ₁₆
C	6 x 32,5 x 48,8	2 ³ / ₈ x 12 ¹³ / ₁₆ x 19 ³ / ₁₆
Unit/Surface	9,92 / m ²	0,92 / ft ²
Qty/row	1,11 m ²	11,94 ft ²
Qty/cube	12,21 m ²	131,34 ft ² 11 rows
Weight/unit avg.	15 kg	33 lb
Weight/cube	1696 kg	3739 lb

Specifications	Codes	Standard Colors
Regular finish	PTR-411R-10	Gray
	PTR-411R-15	Gray and charcoal
	Deluxe Colors	
	PTR-411R-02	Ice gray
	PTR-411R-03	Gray onyx
Smooth Premium finish ①	PTR-411R-24	Travertine beige
	PTR-411R-50	Black
	PTR-411L-21	Ivory beige

Sold together

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 7,04 m² 75,8 ft²



SUPRA CITADIN® M60 SLAB



	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
D	6 x 48,8 x 81,3	2 ³ / ₈ x 19 ³ / ₁₆ x 32
Unit/Surface	2,52 / m ²	0,23 / ft ²
Qty/row	0,79 m ²	8,52 ft ²
Qty/cube	8,71 m ²	93,78 ft ² 11 rows
Weight/unit avg.	57 kg	125 lb
Weight/cube	1240 kg	2728 lb

SPECIFICATIONS	CODES	STANDARD COLORS
Regular finish	PTR-412R-10	Gray
	PTR-412R-15	Gray and charcoal
	DELUXE COLORS	
	PTR-412R-02	Ice gray
	PTR-412R-03	Gray onyx
Smooth Premium finish ①	PTR-412R-24	Travertine beige
	PTR-412R-50	Black
	PTR-412L-21	Ivory beige

Sold separately

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 13,46 m² 144,9 ft²



CITADIN® M60 SMALL RECTANGLE SLAB



	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
E	6 x 16,3 x 32,5	2 ³ / ₈ x 6 ³ / ₈ x 12 ¹³ / ₁₆
Unit/Surface	18,93 / m ²	1,76 / ft ²
Qty/row	1,11 m ²	11,94 ft ²
Qty/cube	12,21 m ²	131,34 ft ² 11 rows
Weight/unit avg.	7,5 kg	16 lb
Weight/cube	1696 kg	3739 lb

SPECIFICATIONS	CODES	COLORS
Regular finish	PTR-413R-10	Gray
	DELUXE COLORS	
	PTR-413R-25	Anthracite brown
Smooth Premium finish ①	PTR-413R-50	Black
	PTR-413L-21	Ivory beige

Sold separately

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 4,82 m² 51,9 ft²

When placing joint filler sand, we recommend using a Teflon-coated vibrating plate on pavers or slabs to protect stone surfaces.

Also we recommend cover snow removal tools with Teflon or neoprene type protectors to minimize the risk of damage from scratches or concrete chips.



RECOUVREMENT CITADIN® 45



	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
	4,5 x 40 x 40	1 ^{3/4} x 15 ^{3/4} x 15 ^{3/4}
Surface/units	0,16 m ²	1,72 ft ²
Qty/row	6 units	
Qty/cube	48 units	8 rows
Weight/unit avg.	16 kg	32 lb
Weight/cube	803 kg	1767 lb

	CODES	STANDARD COLOR
	PMC-411R-15	Gray and charcoal
		DELUXE COLORS
	PMC-411R-02	Ice gray
	PMC-411R-21	Ivory beige
	PMC-411R-24	Travertine beige
	PMC-411R-50	Black

Sold separately


COLORS



● Ice gray



● Gray onyx




● Black



● Ivory beige ⓘ



● Travertine beige



● Gray




● Gray and charcoal




● Anthracite brown


PATTERNS




Pattern 1
Runner pattern




Pattern 2
Modular pattern




Pattern 3
Runner pattern



Pattern 4
Supra checker pattern



Pattern 5
Modular pattern
16% Citadin M60 (60x163x325)
32% Citadin M60 (60x325x325)
36% Citadin M60 (60x325x488)
15% Supra Citadin M60 (60x488x813)



Pattern 6
Modular pattern
3% Citadin M60 (60x163x325)
6% Citadin M60 (60x325x325)
7% Citadin M60 (60x325x488)
83% Supra Citadin M60 (60x488x813)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Flexural (transverse) strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Citadin M60 slab	CSA A2311	5 MPa (725 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	6 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)