


RICHELIEU™ M60 SLAB

CARVED FINISH



RICHELIEU™ M60 SLAB



	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
A	6 x 16,3 x 32,5	2 ³ / ₈ x 6 ³ / ₈ x 12 ¹³ / ₁₆
B	6 x 32,5 x 32,5	2 ³ / ₈ x 12 ¹³ / ₁₆ x 12 ¹³ / ₁₆
C	6 x 32,5 x 48,8	2 ³ / ₈ x 12 ¹³ / ₁₆ x 19 ³ / ₁₆
Unit/Surface	9,92 / m ²	0,92 / ft ²
Qty/row	1,11 m ²	11,94 ft ²
Qty/cube	12,21 m ²	131,34 ft ² 11 rows
Weight/unit avg. moy.	15 kg	33 lb
Weight/cube	1696 kg	3739 lb

SPECIFICATIONS	CODES	STANDARD COLORS
	PTR-310R-13	Sandy gray
	PTR-310R-15	Gray and charcoal
	PTR-310R-35	Ashen beige
		DELUXE COLORS
	PTR-310R-02	Ice gray
	PTR-310R-24	Travertine beige
	PTR-310R-50	Black

Sold together

Approximate coverage areas for one bag of polymeric sand (22,7 kg)

7,04 m²

75,8 ft²



SUPRA RICHELIEU™ M60 SLAB



	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
D	6 x 48,8 x 81,3	2 ³ / ₈ x 19 ³ / ₁₆ x 32
Unit/Surface	2,52 / m ²	0,23 / ft ²
Qty/row	0,79 m ²	8,52 ft ²
Qty/cube	8,71 m ²	93,78 ft ² 11 rows
Weight/unit avg.	57 kg	125 lb
Weight/cube	1240 kg	2728 lb

SPECIFICATIONS	CODES	STANDARD COLORS
	PTR-312R-13	Sandy gray
	PTR-312R-15	Gray and charcoal
		DELUXE COLORS
	PTR-312R-02	Ice gray
	PTR-312R-24	Travertine beige

Sold separately

Approximate coverage areas for one bag of polymeric sand (22,7 kg)

13,46 m²

144,9 ft²

RICHELIEU™ M60 SLAB

CARVED FINISH

COLORS



● Ice gray



● Travertine beige



● Black



● Sandy gray




● Gray and charcoal




● Ashen beige


PATTERNS




Pattern 1
Supra checker pattern




Pattern 2
Runner pattern




Pattern 3
Supra runner pattern



Pattern 4
Modular pattern



Pattern 5
Modular pattern
16% Richelieu M60
(60 x 163 x 325)
32% Richelieu M60
(60 x 325 x 325)
36% Richelieu M60
(60 x 325 x 488)
15% Supra Richelieu M60
(60 x 488 x 813)



Pattern 6
Modular pattern
3% Richelieu M60
(60 x 163 x 325)
6% Richelieu M60
(60 x 325 x 325)
7% Richelieu M60
(60 x 325 x 488)
83% Supra Richelieu M60
(60 x 488 x 813)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Flexural (transverse) strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Richelieu M60 slab	CSA A2311	5 MPa (725 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	6 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)