


RICHELIEU™ M80 PAVER

CARVED FINISH



RICHELIEU™ M80 PAVER



	HEIGHT/WIDTH/LENGTH		
	DIMENSIONS (CM)	DIMENSIONS (IN)	
A	8 x 16,3 x 32,5	3 ¹ / ₈ x 6 ³ / ₈ x 12 ¹³ / ₁₆	
B	8 x 32,5 x 32,5	3 ¹ / ₈ x 12 ¹³ / ₁₆ x 12 ¹³ / ₁₆	
C	8 x 32,5 x 48,8	3 ¹ / ₈ x 12 ¹³ / ₁₆ x 19 ³ / ₁₆	
Units/Surface	9,92 / m ²	0,92 / ft ²	
Qty/row	1,11 m ²	11,94 ft ²	
Qty/cube	8,88 m ²	95,52 ft ²	8 rows
Weight/unit avg.	20 kg	44 lb	
Weight/cube	1643 kg	3622 lb	

SPECIFICATIONS	CODES	STANDARD COLORS
	PPC-310R-13	Sandy gray
	PPC-310R-15	Gray and charcoal
	PPC-310R-35	Ashen beige
		DELUXE COLORS
	PPC-310R-02	Ice gray
	PPC-310R-24	Travertine beige
	PPC-310R-50	Black

Sold together

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 5,28 m² 56,8 ft²



SUPRA RICHELIEU™ M80 PAVER



	HEIGHT/WIDTH/LENGTH		
	DIMENSIONS (CM)	DIMENSIONS (IN)	
D	8 x 48,8 x 81,3	3 ¹ / ₈ x 19 ³ / ₁₆ x 32	
Units/Surface	2,52 / m ²	0,23 / ft ²	
Qty/row	0,79 m ²	8,52 ft ²	
Qty/cube	6,34 m ²	68,20 ft ²	8 rows
Weight/unit avg.	73 kg	161 lb	
Weight/cube	1200 kg	2640 lb	

SPECIFICATIONS	CODES	STANDARD COLORS
	PPC-312R-13	Sandy gray
	PPC-312R-15	Gray and charcoal
		DELUXE COLOR
	PPC-312R-24	Travertine beige

Sold separately

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 10,09 m² 108,57 ft²

RICHELIEU™ M80 PAVER

CARVED FINISH

COLORS



● Ice gray



● Travertine beige



● Black



● Sandy gray




● Gray and charcoal




● Ashen beige


PATTERNS




Pattern 1
Supra runner pattern




Pattern 2
Runner pattern




Pattern 3
Supra runner pattern



Pattern 4
Modular pattern



Pattern 5
Modular pattern
16% Richelieu M80
(80 x 163 x 325)
32% Richelieu M80
(80 x 325 x 325)
36% Richelieu M80
(80 x 325 x 488)
15% Supra Richelieu M80
(80 x 488 x 813)



Pattern 6
Modular pattern
3% Richelieu M80
(80 x 163 x 325)
6% Richelieu M80
(80 x 325 x 325)
7% Richelieu M80
(80 x 325 x 488)
83% Supra Richelieu M80
(80 x 488 x 813)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

INFORMATIONS TECHNIQUES

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Richelieu M80 Paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 po) Width: -1 mm to +2 mm (-1/32 in to + 5/64 po) Height: ±3 mm (±1/8 po)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.