

# AVENUE® TRIANGLE PAVER

## REGULAR OR PREMIUM FINISHES



### TRIANGLE PAVER

	HEIGHT X WIDTH X LENGTH CM / IN	
	10 x 30 x 26	3 <sup>15/16</sup> x 11 <sup>13/16</sup> x 11 <sup>1/4</sup>
Units/Surface	25,62 m <sup>2</sup>	2,38 ft <sup>2</sup>
Qty/row	0,70 m <sup>2</sup>	7,56 ft <sup>2</sup>
Qty/cube	4,92 m <sup>2</sup>	52,92 ft <sup>2</sup>
Weight/cube	1165 kg	2568 lb

Approximate coverage areas for one bag of polymeric sand ( 22,7 kg ) 1,72 m<sup>2</sup>      18,5 ft<sup>2</sup>



### COLORS

-  Granite gray 
-  Light gray 
-  Silver gray
-  Smoke gray
-  Anthracite
-  Opal white 
-  Ivory 
-  Light beige 
-  Sahara beige 
-  Burned beige
-  Sandhill beige
-  Salmon
-  Clay red
-  Red
-  Burgundy
-  Caledonia pink
-  Brown
-  Bistre

### FINISHES

- Smooth Regular
- Grenart Regular
- Smooth Premium 
- Grenart Premium 

### COLORS




Colors with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.


# AVENUE® TRIANGLE PAVER

## REGULAR OR PREMIUM FINISHES

### PATTERN



Pattern 1



Pattern 2

### TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Avenue Triangle paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m <sup>2</sup> (0,74 oz / ft <sup>2</sup> ) after 28 cycles 500 g/m <sup>2</sup> (1,64 oz / ft <sup>2</sup> ) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

### SPECIFICATION CLAUSE

**SPEC. NOTE:** Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC autoblocking Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, color and finish.

#### PART 2 - PRODUCTS

##### 2.1 Precast Concrete Pavers

1. Precast concrete pavers complying with CSA A231.2 and the following prescriptions.
2. AvenueTriangle paver supplied by BOLDUC.
  1. Thickness: 10 cm (3<sup>5</sup>/<sub>16</sub> in)
  2. Nominal Dimensions: 10 x 30 x 26 cm (3<sup>15</sup>/<sub>16</sub> x 11<sup>13</sup>/<sub>16</sub> x 10<sup>1</sup>/<sub>4</sub> in)
  3. Color :
  4. Texture (Regular or Smooth Premium finish or Regular or Grenart premium finish):

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.