


VIA APPIA® 60 PAVER



VIA APPIA® 60 PAVER

	HEIGHT X WIDTH X LENGTH CM / IN	
	6 x 8 to 18 x 12 to 24	2 ^{3/8} x 3 ^{1/8} to 7 x 4 ^{3/4} to 9 ^{1/2}
Units/Surface	44,3 /m ²	4,1 /ft ²
Qty/row	0,97 m ²	10,4 ft ²
Qty/cube	11,62 m ²	125 ft ²
Weight/cube	1617 kg	3558 lb



COLORS



Limestone gray
Garnet red
Sandstone beige
Terracotta brown

Approximate coverage areas for one bag of polymeric sand (22,7 kg)

3,97 m²

42,7 ft²

Shaded colors available on request

COLORS



● Limestone gray



● Sandstone beige




● Terracotta brown




● Garnet red


PATTERNS



Runner pattern



Runner pattern



Runner pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Via Appia 60 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC autoblocking Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, color and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

1. Precast concrete pavers complying with CSA A231.2 and the following prescriptions.
2. Via Appia 60 paver supplied by BOLDUC.
 1. Thickness: 6 cm (2^{3/8} in)
 2. Nominal Dimensions:
 3. Color :
 4. Texture :

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.