

PRESTIGE™ 60 SLAB







PREMIUM FINISHES

PRESTIGE™ 60 SLAB | 40X60



A


	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
A	6 x 40 x 60	2 ^{3/8} x 15 ^{3/4} x 23 ^{5/8}
Unit/Surface	4,17 / m ²	0,39 / ft ²
Qty/row	0,96 m ²	10,33 ft ²
Qty/cube	10,56 m ²	113,63 ft ² 11 rows
Weight/unit avg.	37 kg	81 lb
Weight/cube	1591 kg	3508 lb

SPECIFICATIONS	CODES	COLORS
Grenart Premium finish 	PTR-546G-11	Granite gray 
Grenart Premium finish 	PTR-546G-55	Anthracite
Smooth Premium finish 	PTR-546L-11	Granite gray 
Smooth Premium finish 	PTR-546L-55	Anthracite

Approximate coverage areas for one bag of polymeric sand (22,7 kg)







17,65 m² 190,0 ft²

PRESTIGE™ 60 SLAB | 60X60



B

	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
B	6 x 60 x 60	2 ^{3/8} x 23 ^{5/8} x 23 ^{5/8}
Unit/Surface	2,78 / m ²	0,26 / ft ²
Qty/row	0,72 m ²	7,75 ft ²
Qty/cube	7,92 m ²	85,25 ft ² 11 rows
Weight/unit avg.	56 kg	123 lb
Weight/cube	1200 kg	2646 lb

SPECIFICATIONS	CODES	COLORS
Grenart Premium finish 	PTR-566G-11	Granite gray 
Grenart Premium finish 	PTR-566G-55	Anthracite
Smooth Premium finish 	PTR-566L-11	Granite gray 
Smooth Premium finish 	PTR-566L-55	Anthracite

Sold separately


Approximate coverage areas for one bag of polymeric sand (22,7 kg)


22,06 m² 237,5 ft²

COLORS

GRENART FINISH




● Granite gray 




● Anthracite

SMOOTH FINISH



● Granite gray 




● Anthracite




Colors with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.


PATTERNS



Pattern 1
Checker pattern
(65 x 600 x 600)



Pattern 2
Runner pattern
(65 x 400 x 600)



Pattern 3
Runner pattern
(65 x 600 x 600)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

PRESTIGE™ 60 SLAB

PREMIUM FINISHES

TECHNICAL INFORMATION

Product	Standard	Flexural (transverse) strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Prestige 60 slab	CSA A2311	5 MPa (725 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	6 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)