CITADIN™ 60 SLAB
REGULAR OR SMOOTH PREMIUM ❶ FINISHES

PEDESTRIANS & BICYCLES
CARS
MID-SIZE VEHICLES
HEAVY VEHICLES (2 axles)
HEAVY VEHICLES (3 axles)



CITADIN™ 60 SLAB - 400 x 600

	HEIGHT X WIDTH X LENGTH CM / IN	
*	6 x 40 x 60	$2^{3/8}$ x $15^{3/4}$ x $23^{5/8}$
No. of units	4,2 /m²	0,4 /ft²
Qty/row	0,96 m²	10,33 ft²
Qty/cube	10,56 m²	113,63 ft²
Weight/unit	37 kg	81 lb
Weight/cube	1591 kg	3508 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 17,65 m² 190,0 ft²

COLOURS
Grey and charcoal
Ice grey
Travertine beige
Ivory beige

TEXTURES AND FINISHES
Regular
Smooth Premium ❶



CITADIN™ 60 SLAB - 600 x 600

	HEIGHT X WIDTH X LENGTH CM / IN	
*	6 x 60 x 60	$2^{3/8}$ x $23^{5/8}$ x $23^{5/8}$
No. of units	2,8 /m²	0,3 /ft²
Qty/row	0,72 m²	7,75 ft²
Qty/cube	7,92 m²	85,25 ft²
Weight/unit	56 kg	123 lb
Weight/cube	1200 kg	2646 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 22,06 m² 237,5 ft²

Product on special order for minimum quantity.

COLOURS

REGULAR FINISH


Grey and charcoal


Ice grey



Travertine beige


SMOOTH FINISH ❶



Ivory beige

Colours with solar reflectance indices contributing to the LEED program in order to reduce the creationt of heat islands in urban areas as much as possible.

PATTERNS


Pattern 1
Checker pattern
(60 x 600 x 600)


Pattern 2
Runner pattern
(60 x 400 x 600)


Pattern 3
Runner pattern
(60 x 600 x 600)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

CITADIN™ 60 SLAB
REGULAR OR SMOOTH PREMIUM ❶ FINISHES

TECHNICAL INFORMATIONS

Product	Standard	Flexural (transverse) strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Citadin 60 slab	CSA A231.1	5 MPa (725 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	6 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in Part 2 - Products of section 32 14 13 - Precast Concrete Pavers. It prescribes the choice of BOLDUC pavers and slabs for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, colour and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

.1 Concrete slab complying with CSA-A 231.1 standard and the following prescriptions.

.2 Citadin 60 slab supplied by BOLDUC.

.1 Thickness: 6 cm (2 3/8 in)

.2 Nominal Dimensions:

.3 Colour :

.4 Texture : Regular or Smooth Premium finishes

When placing joint filler sand, we recommend using a Teflon-coated vibrating plate on pavers or slabs to protect stone surfaces.
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA