

CITADIN® M80 PERMEABLE PAVER

REGULAR FINISH




CITADIN® M80 PERMEABLE PAVER

	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
	8 x 16,3 x 32,5	3 ¹¹ / ₈ x 6 ³ / ₈ x 12 ¹³ / ₁₆
	8 mm joint 7,26% opening area	
Units/Surface	18,93 / m ²	1,76 / ft ²
Qty/row	1,11 m ²	11,94 ft ²
Qty/cube	8,88 m ²	95,52 ft ² 8 rows
Weight/unit avg.	10 kg	22 lb
Weight/cube	1643 kg	3622 lb

SPECIFICATIONS	CODES	COULEURS
STANDARD COLOR		
Regular finish	PPC-419R-15	Gray and charcoal
DELUXE COLORS		
Regular finish	PPC-419R-02	Ice gray
Regular finish	PPC-419R-24	Travertine beige


COLORS



● Gray and charcoal



● Ice gray




● Travertine beige



Colors with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.

PATTERN



Runner pattern

TECHNICAL INFORMATION

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Citadin M80 permeable paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)