

CITADIN® M80 PERMEABLE PAVER

REGULAR FINISH



CITADIN® M80 PERMEABLE PAVER

	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
	8 x 16,3 x 32,5	3 ^{1/8} x 6 ^{3/8} x 12 ^{13/16}
	Joint 8mm Ouverture surface 7,26%	
Units/Surface	18,93 / m ²	1,76 / ft ²
Qty/row	1,11 m ²	11,94 ft ²
Qty/cube	8,88 m ²	95,52 ft ² 8 rows
Weight/unit avg.	10 kg	22 lb
Weight/cube	1643 kg	3622 lb

SPECIFICATIONS	CODES	COLORS
Regular finish	PPC-419R-02	Ice gray
	PPC-419R-15	Gray and charcoal

COLORS



● Ice gray




● Gray and charcoal



Colors with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.

PATTERN



Runner pattern

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Citadin M80 permeable paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)