

# PRESTIGE™ 80 PAVER







## PREMIUM FINISHES



### PRESTIGE™ 80 PAVER



	HEIGHT/WIDTH/LENGTH		
	DIMENSIONS (CM)	DIMENSIONS (IN)	
	8 x 40 x 60	3 <sup>1/8</sup> x 15 <sup>3/4</sup> x 23 <sup>5/8</sup>	
Units/Surface	4,17 / m <sup>2</sup>	0,39 / ft <sup>2</sup>	
Qty/row	0,96 m <sup>2</sup>	10,33 ft <sup>2</sup>	
Qty/cube	8,64 m <sup>2</sup>	92,97 ft <sup>2</sup>	9 rows
Weight/unit avg.	45 kg	99 lb	
Weight/cube	1599 kg	3525 lb	

SPECIFICATIONS	CODES	COLORS
Grenart Premium finish 	PPC-546G-11	Granite gray 
Grenart Premium finish 	PPC-546G-55	Anthracite
Smooth Premium finish 	PPC-546L-11	Granite gray 
Smooth Premium finish 	PPC-546L-55	Anthracite


Approximate coverage areas for one bag of polymeric sand ( 22,7 kg )


13,24 m<sup>2</sup>    142,5 ft<sup>2</sup>

## COLORS

### GRENART FINISH




● Granite gray 



● Anthracite

### SMOOTH FINISH



● Granite gray 




● Anthracite




Colors with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.

## PATTERN



Runner pattern  
(80 x 400 x 600)



Checker pattern  
(80 x 400 x 600)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

## TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Prestige 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %): 225 g/m <sup>2</sup> (0,74 oz / ft <sup>2</sup> ) after 28 cycles 500 g/m <sup>2</sup> (1,64 oz / ft <sup>2</sup> ) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.