SUPRA CITADIN® M80 PAVER
REGULAR OR SMOOTH PREMIUM Ⓟ FINISHES

SUPRA CITADIN® M80 PAVER



	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
	8 x 48,8 x 81,3	$3^{1/8}$ x $19^{3/16}$ x 32	
Units/Surface	2,52 / m^2	0,23 / ft^2	
Qty/row	0,79 m^2	8,52 ft^2	
Qty/cube	6,34 m^2	68,20 ft^2	8 rows
Weight/unit	73 kg	161 lb	
Weight/cube	1200 kg	2640 lb	

SPECIFICATIONS	CODES	STANDARD COLOURS
Regular finish	PPC-412R-15	Grey and charcoal
		DELUXE COLOURS
	PPC-412R-02	Ice grey
	PPC-412R-24	Travertine beige
	PPC-412R-50	Black
Premium Ⓟ finish	PPC-412P-02	Ice grey
	PPC-412P-21	Ivory beige

Sold separately

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 10,09 m^2 108,6 ft^2

COLOURS

REGULAR FINISH



● Ice grey



● Black



● Travertine beige



● Grey and charcoal

SMOOTH FINISH Ⓟ




● Ice grey




● Ivory beige

Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.


PATTERN




Pattern 1
Runner pattern



Pattern 4
Supra checker pattern



Pattern 5
Modular pattern
16% Citadin M60 (60x163x325)
32% Citadin M60 (60x325x325)
36% Citadin M60 (60x325x488)
15% Supra Citadin M60 (60x488x813



Pattern 6
Modular pattern
3% Citadin M60 (60x163x325)
6% Citadin M60 (60x325x325)
7% Citadin M60 (60x325x488)
83% Supra Citadin M60 (60x488x813)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Supra Citadin M80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m^2 (0,74 oz / ft^2) after 28 cycles 500 g/m^2 (1,64 oz / ft^2) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

When placing joint filler sand, we recommend using a Teflon-coated vibrating plate on pavers or slabs to protect stone surfaces. Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA