CITADIN™ 80 PAVER
REGULAR OR SMOOTH PREMIUM ❶ FINISHES



CITADIN™ 80 PAVER - 400 x 600

	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
	8 x 40 x 60	$3^{1/8}$ x $15^{3/4}$ x $23^{5/8}$	
Unit/Surface	4,17 / m²	0,39 / ft²	
Qty/row	0,96 m²	10,33 ft²	
Qty/cube	8,64 m²	92,97 ft²	9 rows
Weight/unit	45 kg	99 lb	
Weight/cube	1599 kg	3525 lb	

Specifications	Codes	Standard Colour
Regular finish	PPC-446R-15	Grey and charcoal
		Deluxe Colours
	PPC-446R-02	Ice grey
	PPC-446R-24	Travertine beige
Premium ❶ Finish	PPC-446P-21	Ivory beige

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	13,24 m²	142,5 ft²

COLOURS

REGULAR FINISH



● Grey and charcoal



● Ice grey




● Travertine beige

SMOOTH FINISH ❶




● Ivory beige

PATTERNS



Pattern 1
Runner pattern
(80 x 400 x 600)



Pattern 2
Checker pattern
(80 x 400 x 600)

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Citadin 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

When placing joint filler sand, we recommend using a Teflon-coated vibrating plate on pavers or slabs to protect stone surfaces. Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA