


CLASSIC M60 PAVER

REGULAR FINISH



CLASSIC M60 PAVER



	HEIGHT X WIDTH X LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (PO)
A	6 x 11 x 22	2 ^{3/8} x 4 ^{5/16} x 8 ^{11/16}
B	6 x 22 x 22	2 ^{3/8} x 8 ^{11/16} x 8 ^{11/16}
C	6 x 22 x 33	2 ^{3/8} x 8 ^{11/16} x 13
Units/Surface	20,66 / m ²	1,92 / ft ²
Qty/row	1,06 m ²	11,46 ft ²
Qty/cube	11,71 m ²	126,08 ft ²
Weight/unit avg	6,9 kg	15,2 lb
Weight/cube	1655 kg	3640 lb


SPECIFICATIONS	CODES	STANDARD COLOURS
Regular finish	PPR-811R-13	Sandy gray
	PPR-811R-15	Gray and charcoal
	PPR-811R-32	Sandhill beige
	PPR-811R-50	Charcoal

Approximate coverage areas for one bag of polymeric sand (22,7 kg)


8,12 m²

87,4 ft²


COLOURS




● Sandy gray



● Gray and charcoal




● Sandhill beige




● Charcoal

PATTERNS



Pattern 1
Runner pattern



Pattern 2
Modular pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

TECHNICAL INFORMATION

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Classic M60 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.