LINIA™ 80 PAVER
ULTRA SMOOTH PL FINISH



LINIA™ 80 PAVER

	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
	8 x 6,5 x 26	$3^{1/8}$ x $2^{9/16}$ x $10^{1/4}$	
Units/Surface	59,17 / m^2	5,5 / ft^2	
Qty/row	0,81 m^2	8,73 ft^2	
Qty/cube	6,48 m^2	69,84 ft^2	8 rows
Units/cube	384		
Weight/unit	3,2 kg	7,0 lb	
Weight/cube	1265 kg	2 785 lb	

SPECIFICATIONS	CODES	COLOURS
Ultra smooth platinum finish	PPC-910P-02	Ice grey
Ultra smooth platinum finish	PPC-910P-21	Ivory beige
Ultra smooth platinum finish	PPC-910P-42	Sierra brown
Ultra smooth platinum finish	PPC-910P-50	Black

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 2,89 m^2 31,1 ft^2

COLOURS



Ice grey



Ivory beige




Sierra brown




Black

Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.


PATTERNS




Pattern 1
Runner pattern 1/2




Pattern 2
Runner pattern 1/3




Pattern 3
Herringbone pattern



Pattern 4
45 herringbone pattern



Pattern 5
Basket weave pattern



Pattern 6
Checker pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	orption	Dimensional tolerances
Linia 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m^2 (0,74 oz / ft^2) after 28 cycles 500 g/m^2 (1,64 oz / ft^2) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

Bolduc recommends covering snow-removal tools with Teflon or neoprene-type protectors to minimize the risk of damage from scratches or concrete chipping.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA