CLASSIC™ 50 SLAB
REGULAR FINISH



CLASSIC™ 50 SLAB - 600 x 600

	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)
	5 x 60 x 60	2 x $23^{5/8}$ x $23^{5/8}$
Unit/Surface	2,78 / m^2	0,26 / ft^2
Qty/row	0,72 m^2	7,75 ft^2
Surface/cube	7,92 m^2	85,25 ft^2
Qty/cube	22 units	11 rows
Weight/unit	41,1 kg	90,4 lb
Weight/cube	939 kg	2065 lb

Specifications	Codes	Colours
Regular finish	PTR-866R-15	Gray and charcoal


Approximate coverage areas for one bag of polymeric sand (22,7 kg)	24,43 m^2	262,9 ft^2

COLOURS




● Gray and charcoal

PATTERNS



Pattern 1
Checker pattern



Pattern 2
Runner pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Flexural (transverse) strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Classic 50 slab	CSA A231.1	5 MPa (725 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m^2 (0,74 oz / ft^2) after 28 cycles 500 g/m^2 (1,64 oz / ft^2) after 49 cycles	6 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA

CITADIN™ 60 SLAB
REGULAR FINISH

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA