CITADIN® M60 SLAB
REGULAR OR ULTRA SMOOTH PLATINUM PL FINISHES

CITADIN® M60 SLAB


A


B


C

	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
A	6 x 16,3 x 32,5	$2^{3/8}$ x $6^{3/8}$ x $12^{13/16}$	
B	6 x 32,5 x 32,5	$2^{3/8}$ x $12^{13/16}$ x $12^{13/16}$	
C	6 x 32,5 x 48,8	$2^{3/8}$ x $12^{13/16}$ x $19^{3/16}$	
Unit/Surface	9,92 / m²	0,92 / ft²	
Qty/row	1,11 m²	11,94 ft²	
Qty/cube	12,21 m²	131,34 ft²	11 rows
Weight/unit avg.	15 kg	33 lb	
Weight/cube	1696 kg	3739 lb	

Specifications	Codes	Standard Colours
Regular finish	PTR-411R-15	Grey and charcoal
		Deluxe Colours
	PTR-411R-02	Ice grey
	PTR-411R-24	Travertine beige
	PTR-411R-50	Black
Platinum PL finish	PTR-411P-02	Ice grey
	PTR-411P-21	Ivory beige
	PTR-411P-42	Sierra Brown

Sold together

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	7,04 m²	75,8 ft²

SUPRA CITADIN® M60 SLAB


D

	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
D	6 x 48,8 x 81,3	$2^{3/8}$ x $19^{3/16}$ x 32	
Unit/Surface	2,52 / m²	0,23 / ft²	
Qty/row	0,79 m²	8,52 ft²	
Qty/cube	8,71 m²	93,78 ft²	11 rows
Weight/unit	57 kg	125 lb	
Weight/cube	1240 kg	2728 lb	

SPECIFICATIONS	CODES	STANDARD COLOURS
Regular finish	PTR-412R-15	Grey and charcoal
		DELUXE COLOURS
	PTR-412R-02	Ice grey
	PTR-412R-24	Travertine beige
	PTR-412R-50	Black
Platinum PL finish	PTR-412P-02	Ice grey
	PTR-412P-21	Ivory beige

Sold separately

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	13,46 m²	144,9 ft²

CITADIN® M60 SMALL RECTANGLE SLAB


E

	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
E	6 x 16,3 x 32,5	$2^{3/8}$ x $6^{3/8}$ x $12^{13/16}$	
Unit/Surface	18,93 / m²	1,76 / ft²	
Qty/row	1,11 m²	11,94 ft²	
Qty/cube	12,21 m²	131,34 ft²	11 rows
Weight/unit	7,5 kg	16 lb	
Weight/cube	1696 kg	3739 lb	

SPECIFICATIONS	CODES	DELUXE COLOURS
Regular finish	PTR-413R-25	Anthracite brown
	PTR-413R-50	Black

Sold separately

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	4,82 m²	51,9 ft²

RECOUVREMENT CITADIN® 45



	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)
	4,5 x 40 x 40	$1^{3/4}$ x $15^{3/4}$ x $15^{3/4}$
Surface/units	0,16 m^2	1,72 ft^2
Qty/row	6 units	
Qty/cube	48 units	8 rows
Weight/unit	16 kg	32 lb
Weight/cube	803 kg	1767 lb

Sold separately

CODES	STANDARD COLOUR
PMC-411R-15	Grey and charcoal
	DELUXE COLOURS
PMC-411R-02	Ice grey
PMC-411R-21	Ivory beige
PMC-411R-24	Travertine beige
PMC-411R-50	Black

COLOURS

REGULAR FINISH



Ice grey



Black



Travertine beige



Grey and charcoal



Anthracite brown

Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.

ULTRA SMOOTH FINISH



Ice grey




Ivory beige




Sierra brown


PATTERNS




Pattern 1
Runner pattern




Pattern 2
Modular pattern




Pattern 3
Runner pattern



Pattern 4
Supra checker pattern



Pattern 5
Modular pattern
16% Citadin M60 (60x163x325)
32% Citadin M60 (60x325x325)
36% Citadin M60 (60x325x488)
15% Supra Citadin M60
(60x488x813



Pattern 6
Modular pattern
3% Citadin M60 (60x163x325)
6% Citadin M60 (60x325x325)
7% Citadin M60 (60x325x488)
83% Supra Citadin M60
(60x488x813)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Flexural (transverse) strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Citadin M60 slab	CSA A231.1	5 MPa (725 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m^2 (0,74 oz / ft^2) after 28 cycles 500 g/m^2 (1,64 oz / ft^2) after 49 cycles	6 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

When placing joint filler sand, we recommend using a Teflon-coated vibrating plate on pavers or slabs to protect stone surfaces. Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA