CITADIN® M80 PERMEABLE PAVER
REGULAR FINISH



CITADIN® M80 PERMEABLE PAVER

	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
	8 x 16,3 x 32,5	$3^{1/8}$ x $6^{3/8}$ x $12^{13/16}$	
	8 mm joint | 7,26% opening area		
Units/Surface	18,93 / m^2	1,76 / ft^2	
Qty/row	1,11 m^2	11,94 ft^2	
Qty/cube	8,88 m^2	95,52 ft^2	8 rows
Weight/unit	10 kg	22 lb	
Weight/cube	1643 kg	3622 lb	

SPECIFICATIONS	CODES	STANDARD COLOUR
Regular finish	PPC-419R-15	Grey and charcoal
		DELUXE COLOUR
	PPC-419R-02	Ice grey

COLOURS




● Grey and charcoal



● Ice grey

Colours with solar reflectance indices contributing to the LEED program in order to reduce the creationt of heat islands in urban areas as much as possible.

PATTERN



Runner pattern

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Citadin M80 permeable paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m^2 (0,74 oz / ft^2) after 28 cycles 500 g/m^2 (1,64 oz / ft^2) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA