
CLASSIC M60 PAVER
REGULAR FINISH

CLASSIC M60 PAVER




	HEIGHT X WIDTH X LENGTH DIMENSIONS (CM)	DIMENSIONS (PO)	
A	6 x 11 x 22	$2^{3/8}$ x $4^{5/16}$ x $8^{11/16}$	
B	6 x 22 x 22	$2^{3/8}$ x $8^{11/16}$ x $8^{11/16}$	
C	6 x 22 x 33	$2^{3/8}$ x $8^{11/16}$ x 13	
Units/Surface	20,66 / m^2	1,92 / ft^2	
Qty/row	1,06 m^2	11,46 ft^2	
Qty/cube	11,71 m^2	126,08 ft^2	11 rows
Weight/unit avg	6,9 kg	15,2 lb	
Weight/cube	1655 kg	3640 lb	

SPECIFICATIONS	CODES	STANDARD COLOURS
Regular finish	PPR-811R-13	Sandy grey
	PPR-811R-15	Grey and charcoal
	PPR-811R-32	Sandhill beige
	PPR-811R-50	Charcoal

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	8,12 m^2	87,4 ft^2

COLOURS



Sandy grey



Grey and charcoal


Sandhill beige


Charcoal

PATTERNS


Pattern 1
Runner pattern


Pattern 2
Modular pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Classic M60 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m^2 (0,74 oz / ft^2) after 28 cycles 500 g/m^2 (1,64 oz / ft^2) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA