HEXAGON™ 80 PAVER
SMOOTH PREMIUM FINISH



HEXAGON™ 80 PAVER


	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
	8 x 20 x 23	$3^{1/8}$ x $7^{7/8}$ x $9^{1/8}$	
Units/Surface	28,57 / m^2	2,7 / ft^2	
Qty/row	0,97 m^2	10,44 ft^2	
Qty/cube	9,7 m^2	104,4 ft^2	10 rows
Weight/unit avg.	6 kg	14 lb	
Weight/cube	1792 kg	3943 lb	


SPECIFICATIONS	CODES	COLOURS
Smooth premium finish	PPC-990L-02	Ice grey
	PPC-990L-11	Granite grey
	PPC-990L-21	Ivory beige
	PPC-990L-25	Anthracite brown
	PPC-990L-50	Black

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	5,77 m^2	62,1 ft^2


COLOURS


Ice grey


Granite grey



Black


Ivory beige


Anthracite brown

Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.

PATTERN



Runner pattern
(20 x 23)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Hexagon 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m^2 (0,74 oz / ft^2) after 28 cycles 500 g/m^2 (1,64 oz / ft^2) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA