PRESTIGE™ 60 SLAB
PREMIUM FINISHES

PRESTIGE™ 60 SLAB | 40X60



A

		HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
	A	6 x 40 x 60	$2^{3/8}$ x $15^{3/4}$ x $23^{5/8}$	
Unit/Surface		4,17 / m²	0,39 / ft²	
Qty/row		0,96 m²	10,33 ft²	
Qty/cube		10,56 m²	113,63 ft²	11 rows
Weight/unit avg.		37 kg	81 lb	
Weight/cube		1591 kg	3508 lb	

SPECIFICATIONS	CODES	COLOURS
Grenart Premium finish	PTR-546G-11	Granite grey
	PTR-546G-55	Anthracite
Smooth Premium finish	PTR-546L-11	Granite grey
	PTR-546L-55	Anthracite

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 17,65 m² 190,0 ft²

PRESTIGE™ 60 SLAB | 60X60



B

		HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
	B	6 x 60 x 60	$2^{3/8}$ x $23^{5/8}$ x $23^{5/8}$	
Unit/Surface		2,78 / m²	0,26 / ft²	
Qty/row		0,72 m²	7,75 ft²	
Qty/cube		7,92 m²	85,25 ft²	11 rows
Weight/unit avg.		56 kg	123 lb	
Weight/cube		1200 kg	2646 lb	

SPECIFICATIONS	CODES	COLOURS
Grenart Premium finish	PTR-566G-11	Granite grey
	PTR-566G-55	Anthracite
Smooth Premium finish	PTR-566L-11	Granite grey
	PTR-566L-55	Anthracite

Sold separately

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 22,06 m² 237,5 ft²

COLOURS

GRENART FINISH



● Granite grey



● Anthracite

SMOOTH FINISH




● Granite grey




● Anthracite

Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.


PATTERNS



Pattern 1
Checker pattern
(65 x 600 x 600)



Pattern 2
Runner pattern
(65 x 400 x 600)



Pattern 3
Runner pattern
(65 x 600 x 600)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA

PRESTIGE™ 60 SLAB
PREMIUM FINISHES

TECHNICAL INFORMATIONS

Product	Standard	Flexural (transverse) strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Prestige 60 slab	CSA A231.1	5 MPa (725 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	6 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA