PRESTIGE™ 80 PAVER
PREMIUM FINISHES

PRESTIGE™ 80 PAVER



	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
	8 x 40 x 60	$3^{1/8}$ x $15^{3/4}$ x $23^{5/8}$	
Units/Surface	4,17 / m²	0,39 / ft²	
Qty/row	0,96 m²	10,33 ft²	
Qty/cube	8,64 m²	92,97 ft²	9 rows
Weight/unit avg.	45 kg	99 lb	
Weight/cube	1599 kg	3525 lb	

SPECIFICATIONS	CODES	COLOURS
Grenart Premium finish	PPC-546G-11	Granite grey
	PPC-546G-55	Anthracite
Smooth Premium finish	PPC-546L-11	Granite grey
	PPC-546L-55	Anthracite

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	13,24 m²	142,5 ft²

COLOURS

GRENART FINISH



● Granite grey



● Anthracite

SMOOTH FINISH




● Granite grey




● Anthracite

Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.

PATTERN



Runner pattern
(80 x 400 x 600)



Checker pattern
(80 x 400 x 600)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Prestige 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA