RICHELIEU™ M60 SLAB
CARVED FINISH


A


B


C

RICHELIEU™ M60 SLAB

	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
A	6 x 16,3 x 32,5	$2^{3/8}$ x $6^{3/8}$ x $12^{13/16}$	
B	6 x 32,5 x 32,5	$2^{3/8}$ x $12^{13/16}$ x $12^{13/16}$	
C	6 x 32,5 x 48,8	$2^{3/8}$ x $12^{13/16}$ x $19^{3/16}$	
Unit/Surface	9,92 / m²	0,92 / ft²	
Qty/row	1,11 m²	11,94 ft²	
Qty/cube	12,21 m²	131,34 ft²	11 rows
Weight/unit avg. moy.	15 kg	33 lb	
Weight/cube	1696 kg	3739 lb	

SPECIFICATIONS	CODES	STANDARD COLOURS
	PTR-310R-13	Sandy grey
	PTR-310R-15	Grey and charcoal
	PTR-310R-35	Ashen beige
		DELUXE COLOURS
	PTR-310R-02	Ice grey
	PTR-310R-24	Travertine beige
	PTR-310R-50	Black

Sold together

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	7,04 m²	75,8 ft²

SUPRA RICHELIEU™ M60 SLAB


D

	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)	
D	6 x 48,8 x 81,3	$2^{3/8}$ x $19^{3/16}$ x 32	
Unit/Surface	2,52 / m²	0,23 / ft²	
Qty/row	0,79 m²	8,52 ft²	
Qty/cube	8,71 m²	93,78 ft²	11 rows
Weight/unit avg.	57 kg	125 lb	
Weight/cube	1240 kg	2728 lb	

SPECIFICATIONS	CODES	STANDARD COLOURS
	PTR-312R-13	Sandy grey
	PTR-312R-15	Grey and charcoal
		DELUXE COLOURS
	PTR-312R-02	Ice grey
	PTR-312R-24	Travertine beige

Sold separately

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	13,46 m²	144,9 ft²

RICHELIEU™ M60 SLAB
CARVED FINISH

COLOURS


Ice grey


Travertine beige


Black



Sandy grey



Grey and charcoal



Ashen beige


Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.


PATTERNS



Pattern 1
Supra checker pattern


Pattern 2
Runner pattern


Pattern 3
Supra runner pattern


Pattern 4
Modular pattern


Pattern 5
Modular pattern
16% Richelieu M60
(60 x 163 x 325)
32% Richelieu M60
(60 x 325 x 325)
36% Richelieu M60
(60 x 325 x 488)
15% Supra Richelieu M60
(60 x 488 x 813)


Pattern 6
Modular pattern
3% Richelieu M60
(60 x 163 x 325)
6% Richelieu M60
(60 x 325 x 325)
7% Richelieu M60
(60 x 325 x 488)
83% Supra Richelieu M60
(60 x 488 x 813)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of slabs resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Flexural (transverse) strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Richelieu M60 slab	CSA A231.1	5 MPa (725 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	6 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA