
RICHELIEU™ M80 PAVER
CARVED FINISH



RICHELIEU™ M80 PAVER

	HEIGHT/WIDTH/LENGTH DIMENSIONS (CM)	DIMENSIONS (IN)
A	8 x 16,3 x 32,5	$3^{1/8}$ x $6^{3/8}$ x $12^{13/16}$
B	8 x 32,5 x 32,5	$3^{1/8}$ x $12^{13/16}$ x $12^{13/16}$
C	8 x 32,5 x 48,8	$3^{1/8}$ x $12^{13/16}$ x $19^{3/16}$
Units/Surface	9,92 / m²	0,92 / ft²
Qty/row	1,11 m²	11,94 ft²
Qty/cube	8,88 m²	95,52 ft² 8 rows
Weight/unit avg.	20 kg	44 lb
Weight/cube	1643 kg	3622 lb

SPECIFICATIONS	CODES	STANDARD COLOURS
	PPC-310R-13	Sandy grey
	PPC-310R-15	Grey and charcoal
	PPC-310R-35	Ashen beige
		DELUXE COLOURS
	PPC-310R-02	Ice grey
	PPC-310R-24	Travertine beige
	PPC-310R-50	Black

Sold together

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	5,28 m²	56,8 ft²

COLOURS


Ice grey


Travertine beige


Black



Sandy grey



Grey and charcoal



Ashen beige


Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.


PATTERNS



Pattern 1
Supra runner pattern


Pattern 2
Runner pattern


Pattern 3
Supra runner pattern


Pattern 4
Modular pattern


Pattern 5
Modular pattern
16% Richelieu M80
(80 x 163 x 325)
32% Richelieu M80
(80 x 325 x 325)
36% Richelieu M80
(80 x 325 x 488)
15% Supra Richelieu M80
(80 x 488 x 813)


Pattern 6
Modular pattern
3% Richelieu M80
(80 x 163 x 325)
6% Richelieu M80
(80 x 325 x 325)
7% Richelieu M80
(80 x 325 x 488)
83% Supra Richelieu M80
(80 x 488 x 813)

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

INFORMATIONS TECHNIQUES

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Richelieu M80 Paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %) : 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 po)Width: -1 mm to +2 mm (-1/32 in to + 5/64 po)Height: ±3 mm (±1/8 po)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA