
APPIALOCK 100® PAVER





APPIALOCK 100® PAVER

	HEIGHT X WIDTH X LENGTH CM / IN	
	10 x 14 x 22	4 x $5^{1/2}$ x $8^{5/8}$
Units/Surface	32,5 /m^2	3,0 /ft^2
Qty/row	0,99 m^2	10,61 ft^2
Qty/cube	6,90 m^2	74,30 ft^2
Weight/cube	1648 kg	3626 lb

COLOURS

Limestone grey
Garnet red
Sandstone beige
Terracotta brown
Black

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 2,27 m^2 24,4 ft^2

Shaded colours available on request

Edge paver (one straight side) and half-paver also available

COLOURS


Limestone grey



Sandstone beige


Terracotta brown


Garnet red


Black

PATTERN



Runner Pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Appialock 100 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m^2 (0,74 oz / ft^2) after 28 cycles 500 g/m^2 (1,64 oz / ft^2) after 49 cycles	5 % maximum	Lenght: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in Part 2 - Products of section 02751 - Prefabricated Concrete Pavers. It permits the specification of Bolduc interlocking pavers as a surface covering and lists the requirements for geometric and physical characteristics. It also indicates the dimensions and colour of the selected interlocking paver.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

.1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.

.2 Appialock 100 paver supplied by BOLDUC.

.1 Thickness: 10 cm (4 in)

.2 Nominal Dimensions: 10 x 14 x 22 cm (4 x $5^{1/2}$ x $8^{5/8}$ in)

.3 Colour :

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA