AVENUE 100 SL PAVER
REGULAR OR PREMIUM FINISHES


PEDESTRIANS & BICYCLES
CARS
MID-SIZE VEHICLES
HEAVY VEHICLES (2 axles)
HEAVY VEHICLES (3 axles)



AVENUE AUTOBLOCKING SL 100 PAVER

	HEIGHT X WIDTH X LENGTH CM / IN	
	10 x 15 x 30	$3^{15/16}$ x $5^{7/8}$ x $11^{13/16}$
Units/Surface	22,2 m^2	2,06 ft^2
Qty/row	1,08 m^2	11,63 ft^2
Qty/cube	7,56 m^2	81,38 ft^2
Weight/cube	1805 kg	3970 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	2,70 m^2	29,1 ft^2



	HEIGHT X WIDTH X LENGTH CM / IN	
	10 x 30 x 30	$3^{15/16}$ x $11^{13/16}$ x $11^{13/16}$
Units/Surface	11,10 m^2	1,03 ft^2
Qty/row	1,08 m^2	11,63 ft^2
Qty/cube	7,56 m^2	81,38 ft^2
Weight/cube	1805 kg	3970 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	4,00 m^2	43,0 ft^2

Product on special order for minimum quantity.


COLOURS
- Granite grey
- Light grey
- Silver grey
- Smoke grey
- Anthracite
- Opal white
- Ivory
- Light beige
- Sahara beige
- Burned beige
- Sandhill beige
- Salmon
- Clay red
- Red
- Burgundy
- Caledonia pink
- Brown
- Bistre

TEXTURES AND FINISHES
- Smooth regular
- Grenart regular
- Ground regular
- Smooth Premium
- Grenart Premium
- Ground Premium

COLOURS


Granite grey


Light grey


Silver grey


Smoke grey



Anthracite



Opal white



Ivory



Light beige



Sahara beige



Burned beige



Sandhill beige



Salmon


Clay red


Red


Burgundy


Caledonia pink


Brown


Bistre


Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.


BOLDUC
CONCRETE PRODUCT MANUFACTURER


CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA


AVENUE 100 SL PAVER
REGULAR OR PREMIUM FINISHES


PATTERN



Herringbone pattern



Checker pattern


Checker pattern 45°


Runner pattern


Runner pattern


Runner pattern45°


Backet weave pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Avenue 100 SL paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	5 % maximum	Lenght: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC autoblocking Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, colour and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

.1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.

.2 Avenue 100 SL paver supplied by BOLDUC.

.1 Thickness: 10 cm ($3^{15/16}$ in)

.2 Nominal Dimensions:

.3 Colour :

.4 Texture (Smooth Regular or Premium, Grenart Regular or Premium or Ground Regular or Premium Finishes):

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.