# AVENUE® 100 TRIANGLE PAVER - 300 x 256
## REGULAR OR PREMIUM FINISHES



PEDESTRIANS & BICYCLES
CARS
MID-SIZE VEHICLES
HEAVY VEHICLES (2 axles)
HEAVY VEHICLES (3 axles)

### AVENUE 100 TRIANGLE PAVER - 300 x 256

| | HEIGHT X WIDTH X LENGTH CM / IN | |
|---|---|---|
| | 10 x 30 x 26 | $3^{15/16}$ x $11^{13/16}$ x $11^{1/4}$ |
| Units/Surface | 25,62 m² | 2,38 ft² |
| Qty/row | 0,70 m² | 7,56 ft² |
| Qty/cube | 4,92 m² | 52,92 ft² |
| Weight/cube | 1165 kg | 2568 lb |

| | | |
|---|---|---|
| Approximate coverage areas for one bag of polymeric sand ( 22,7 kg ) | 1,72 m² | 18,5 ft² |

Product on special order for minimum quantity.

COLOURS

- Granite grey
- Light grey
- Silver grey
- Smoke grey
- Anthracite
- Opal white
- Ivory
- Light beige
- Sahara beige
- Burned beige
- Sandhill beige
- Salmon
- Clay red
- Red
- Burgundy
- Caledonia pink
- Brown
- Bistre


TEXTURES AND FINISHES

- Smooth Regular
- Grenart Regular
- Smooth Premium
- Grenart Premium

### COLOURS


Granite grey


Light grey


Silver grey


Smoke grey



Anthracite



Opal white



Ivory



Light beige



Sahara beige



Burned beige



Sandhill beige



Salmon


Clay red


Red


Burgundy


Caledonia pink



Brown


Bistre


Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.

# **AVENUE® 100 TRIANGLE PAVER** - 300 x 256
REGULAR OR PREMIUM FINISHES

## PATTERN



Pattern 1



Pattern 2

## TECHNICAL INFORMATIONS

| Product | Standard | Compressive strength | Durability to freeze-thaw cycles with utilisation of de-icing salts | Water absorption | Dimensional tolerances |
|---|---|---|---|---|---|
| **Avenue 100 Triangle paver 300 x 256** | CSA A231.2 | 50 MPa (7250 psi) | Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles | 5 % maximum | Lenght: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in) |

## SPECIFICATION CLAUSE

**SPEC. NOTE:** Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, colour and finish.

**PART 2 - PRODUCTS**

**2.1 Precast Concrete Pavers**

.1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.

.2 Avenue 100 Triangle paver 300 x 256 supplied by BOLDUC.

.1 Thickness: 10 cm ($3^{15/16}$ in)

.2 Nominal Dimensions: 10 x 30 x 26 cm ($3^{15/16}$ x $11^{13/16}$ x $10^{1/4}$ in)

.3 Colour :

.4 Texture (Smooth Regular or Premium or Grenart Regular or Premium) :

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA