CITADIN™ 80 PAVER
REGULAR OR SMOOTH PREMIUM ❶ FINISHES

PEDESTRIANS & BICYCLES
CARS
MID-SIZE VEHICLES
HEAVY VEHICLES (2 axles)
HEAVY VEHICLES (3 axles)

CITADIN ™ 80 PAVER



	HEIGHT X WIDTH X LENGTH CM / IN	
	8 x 40 x 60	$3^{1/8}$ x $15^{3/4}$ x $23^{5/8}$
Units/Surface	4,17 /m²	0,39 /ft²
Qty/row	0,96 m²	10,33 ft²
Qty/cube	8,64 m²	92,97 ft²
Weight/unit	45 kg	99 lb
Weight/cube	1599 kg	3525 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 13,24 m² 142,5 ft²

COLOURS

Regular finish
Grey and charcoal
Ice grey
Travertine beige

Smooth Premium ❶ finish
Ivory beige

COLOURS


● Grey and charcoal



● Ice grey



● Travertine beige


● Ivory beige ❶

Colours with solar reflectance indices contributing
to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.

PATTERNS


Pattern 1
Runner pattern
(80 x 400 x 600)


Pattern 2
Checker pattern
(80 x 400 x 600)

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Citadin 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	5 % maximum	Lenght: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, colour and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

.1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.
.2 Citadin 80 paver supplied by BOLDUC.
.1 Thickness: 8 cm ($3^{1/8}$ in)
.2 Nominal Dimensions:
.3 Colour :
.4 Texture : Regular or Smooth Premium Finishes

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA