
CLASSIC[MC] 80 PAVER



CLASSIC[MC] 80 PAVER



HEIGHT X WIDTH X LENGTH CM / IN		
	8 x 10,8 x 21,6	$3^{1/8}$ x $4^{1/4}$ x $8^{1/2}$
Units/Surface	43,52 /m²	4,0 /ft²
Qty/cube	9,33 m²	100,4 ft²
Weight/cube	1728 kg	3802 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	4,00 m²	43,0 ft²

COLOURS
- Grey
- Black
- Avenue (1)

Note 1: Prices for Avenue colours and finishes are available upon request.



HEIGHT X WIDTH X LENGTH CM / IN		
	8 x 25 x 25	$3^{1/8}$ x $9^{13/16}$ x $9^{13/16}$
Units/Surface	16 /m²	1,5 /ft²
Qty/cube	8,46 m²	91,08 ft²
Weight/cube	1568 kg	3457 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	6,00 m²	64,6 ft²

Product on special order for minimum quantity.

COLOURS



Grey


Black

AVENUE SERIES COLOURS


Granite grey


Light grey


Silver grey


Smoke grey



Anthracite



Opal white


Ivory



Light beige



Sahara beige



Burned Beige



Sandhill beige



Salmon


Clay red


Red


Burgundy


Caledonia pink


Brown


Bistre

Avenue Series colours and finishes are available upon request, minimum quantity required.


Colours contributing to LEED program solar reflective indices can help reduce the heat island effect in urban settings.


BOLDUC
CONCRETE PRODUCT MANUFACTURER


CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA


CLASSIC[MC] 80 PAVER


PATTERNS



Herringbone pattern


Checker pattern


Checker pattern 45°


Runner pattern


Runner pattern


Basket weave pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Classic 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	5 % maximum	Lenght: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, colour and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

.1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.

.2 Classic 80 paver supplied by BOLDUC.

.1 Thickness: 8 cm (3⅛ in)

.2 Nominal Dimensions:

.3 Colour :

.4 Texture (Regular finish) :

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.