HEXAGON™ 80 PAVER
PREMIUM FINISH



PEDESTRIANS & BICYCLES
CARS
MID-SIZE VEHICLES
HEAVY VEHICLES (2 axles)
HEAVY VEHICLES (3 axles)

HEXAGON™ 80 PAVER

	HEIGHT X WIDTH X LENGTH CM / IN		
	8 x 20 x 23	$3^{1/8}$ x $7^{7/8}$ x $9^{1/8}$	
Units/Surface	28,57 /m^2	2,7 / ft^2	
Qty/row	0,97 m^2	10,44 ft^2	
Qty/cube	9,7 m^2	104,4 ft^2	10 rows
Weight/unit	6,3 kg	13,86 lb	
Weight/cube	1792 kg	3943 lb	

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	5,77 m^2	62,1 ft^2

COLOURS
Granite grey (2)
Black (2)
Avenue (1)
Certain colours in the Avenue series contribute to the LEED program.

TEXTURE AND FINISH
Smooth Premium
Avenue (1)


Product on special order for minimum quantity.

Note 1: Prices for Avenue colours and finishes are available upon request.
Note 2: Products available from inventory.

COLOURS



Granite grey



Black


AVENUE SERIES COLOURS



Granite grey



Light grey



Silver grey



Smoke grey



Anthracite



Opal white




Ivory



Light beige



Sahara beige




Burned Beige




Sandhill beige




Salmon




Clay red



Red



Burgundy



Caledonia pink



Brown




Bistre

Avenue Series colours and finishes are available upon request, minimum quantity required.

Colours contributing to LEED program solar reflective indices can help reduce the heat island effect in urban settings.

PATTERN



The layout shown in the above illustration is for information purposes only. Bolduc disclaims allresponsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA

HEXAGON™ 80 PAVER
PREMIUM FINISH

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Hexagon 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	5 % maximum	Lenght: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, colour and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

.1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.

.2 Hexagon 80 paver supplied by BOLDUC.

.1 Thickness: 8 cm (3 1/8 in)

.2 Nominal Dimensions:8 x 20 x 23 cm (31/8 x 77/8 x 91/8 in)

.3 Colour :

.4 Texture (Smooth Premium finish)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.