
PRESTIGE™ 60 PAVER
PREMIUM FINISHES



PRESTIGE™ 60 PAVER



	HEIGHT X WIDTH X LENGTH CM / IN	
	6 x 10 x 20	$2^{3/8}$ x $3^{15/16}$ x $7^{7/8}$
Units/Surface	50 /m²	4,7 /ft²
Qty/cube	10,56 m²	113,7 ft²
Weight/cube	1591 kg	3508 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 4,56 m² 49,1 ft²



	HEIGHT X WIDTH X LENGTH CM / IN	
	6 x 20 x 20	$2^{3/8}$ x $7^{7/8}$ x $7^{7/8}$
Units/Surface	25 /m²	2,3 /ft²
Qty/cube	10,56 m²	113,7 ft²
Weight/cube	1591 kg	3508 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 6,82 m² 73,4 ft²

One size per cube

COLOURS
- Granite grey
- Anthracite
- Avenue (1)

TEXTURES AND FINISH
- Grenart Premium
- Smooth Premium
- Avenue (1)

Note 1: Prices for Avenue colours and finishes are available upon request.

Product on special order for minimum quantity.

COLOURS

GRENART FINISH


Granite grey


Anthracite

SMOOTH FINISH


Granite grey


Anthracite

Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.

AVENUE SERIES COLOURS


Granite grey


Light grey


Silver grey


Smoke grey


Anthracite


Opal white


Ivory



Light beige



Sahara beige


Burned Beige



Sandhill beige



Salmon



Clay red


Red


Burgundy


Caledonia pink


Brown


Bistre

Avenue Series colours and finishes are available upon request, minimum quantity required.


Colours contributing to LEED program solar reflective indices can help reduce the heat island effect in urban settings.

BOLDUC
CONCRETE PRODUCT MANUFACTURER


CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA

PRESTIGE™ 60 PAVER
PREMIUM FINISHES

PATTERNS



Checker pattern



Runner pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Prestige 60 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	5 % maximum	Lenght: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, colour and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

.1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.

.2 Prestige 60 paver supplied by BOLDUC.

.1 Thickness: 6 cm ($2^{3/8}$ in)

.2 Nominal Dimensions:

.3 Colour :

.4 Texture : Smooth Premium or Grenart Premium finishes

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA