
PRESTIGE™ 80 PAVER
PREMIUM FINISHES



PRESTIGE™ 80 PAVER



	HEIGHT X WIDTH X LENGTH CM / IN	
	8 x 20 x 40	$3^{1/8}$ x $7^{7/8}$ x $15^{3/4}$
Units/Surface	12,5 /m²	1,16 /ft²
Qty/row	0,96 m²	10,33 ft²
Qty/cube	8,64 m²	92,97 ft²
Weight/unit	15 kg	33 lb
Weight/cube	1599 kg	3525 lb
Approximate coverage areas for one bag of polymeric sand (22,7 kg)	7,37 m²	79,3 ft²



	HEIGHT X WIDTH X LENGTH CM / IN	
	8 x 40 x 40	$3^{1/8}$ x $15^{3/4}$ x $15^{3/4}$
Units/Surface	6,25 /m²	0,58 /ft²
Qty/row	0,96 m²	10,33 ft²
Qty/cube	8,64 m²	92,97 ft²
Weight/unit	30 kg	66 lb
Weight/cube	1599 kg	3525 lb
Approximate coverage areas for one bag of polymeric sand (22,7 kg)	11,04 m²	118,8 ft²



	HEIGHT X WIDTH X LENGTH CM / IN	
*	8 x 40 x 60	$3^{1/8}$ x $15^{3/4}$ x $23^{5/8}$
Units/Surface	4,17 /m²	0,39 /ft²
Qty/row	0,96 m²	10,33 ft²
Qty/cube	8,64 m²	92,97 ft²
Weight/unit	45 kg	99 lb
Weight/cube	1599 kg	3525 lb
Approximate coverage areas for one bag of polymeric sand (22,7 kg)	13,24 m²	142,5 ft²

COLOURS

- Granite grey (2*)
- Anthracite (2*)
- Avenue (1)

TEXTURES AND FINISH

- Grenart Premium
- Smooth Premium
- Avenue (1)

Note 1: Prices for Avenue colours and finishes are available upon request.

Note 2: Products available from inventory.

Product on special order for minimum quantity.

COLOURS

GRENART FINISH



● Granite grey



● Anthracite

SMOOTH FINISH



● Granite grey



● Anthracite

Colours with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA

PRESTIGE™ 80 PAVER
PREMIUM FINISHES

AVENUE SERIES COLOURS


Granite grey


Light grey


Silver grey


Smoke grey



Anthracite


Opal white



Ivory



Light beige



Sahara beige



Burned Beige



Sandhill beige



Salmon


Clay red


Red


Burgundy


Caledonia pink



Brown



Bistre


Avenue Series colours and finishes are available upon request, minimum quantity required.


Colours contributing to LEED program solar reflective indices can help reduce the heat island effect in urban settings.


PATTERNS



Checker pattern


Runner pattern


Runner pattern


Runner pattern


Runner pattern


Modular pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Prestige 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	5 % maximum	Lenght: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, colour and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

.1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.

.2 Prestige 80 paver supplied by BOLDUC.

.1 Thickness: 8 cm (3 1/8 in)

.2 Nominal Dimensions:

.3 Colour :

.4 Texture : Smooth Premium or Grenart Premium finishes

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA