

TRI-APPIA 100™ PAVER



TRI-APPIA 100 ™ PAVER



	HEIGHT X WIDTH X LENGTH CM / IN	
A	10 x 12,5 x 20	4 x $4^{15/16}$ x $7^{7/8}$
B	10 x 12,5 x 25	4 x $4^{15/16}$ x $9^{7/8}$
C	10 x 12,5 x 30	4 x $4^{15/16}$ x $11^{13/16}$
Units/Surface	32 /m^2	2,97 /ft^2
Qty/row	0,94 m^2	10,09 ft^2
Qty/cube	7,52 m^2	80,72 ft^2
Weight/cube	1790 kg	3938 lb

COLOURS

- Limestone grey
- Garnet red
- Sandstone beige
- Terracotta brown
- Black

Shaded colours available on request

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 2,27 m^2 24,4 ft^2

The three formats can be found on the same cube

Product on special order for minimum quantity.

COLOURS


Limestone grey



Sandstone beige



Terracotta brown


Garnet red


Black

PATTERNS


Runner pattern


Runner pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

BOLDUC
CONCRETE PRODUCT MANUFACTURER

CANADA : 1 800 463-8966
USA : 1 800 603-5567
WWW.BOLDUC.CA

TRI-APPIA 100™ PAVER

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Tri-Appia 100 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	5 % maximum	Lenght: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Nclude the following article in Part 2 - Products of section 02751 - Prefabricated Concrete Pavers. It permits the specification of Bolduc pavers as a surface covering and lists the requirements for geometric and physical characteristics. It also indicates the dimensions and colour of the selected interlocking paver.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

.1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.

.2 Tri-Appia 100 paver supplied by BOLDUC.

.1 Thickness: 10 cm (4 in)

.2 Nominal Dimensions: 10 x 12,5 x 20, 25, 30 cm (4 x $4^{15/16}$ x $7^{7/8}$, $9^{7/8}$, $11^{13/16}$ in)

.3 Colour :

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.