VIA APPIA® 80 PAVER

PEDESTRIANS & BICYCLES
CARS
MID-SIZE VEHICLES
HEAVY VEHICLES (2 axles)
HEAVY VEHICLES (3 axles)

VIA APPIA® 80 PAVER



	HEIGHT X WIDTH X LENGTH CM / IN	
Module 1	8 x 8 to 12 x 12 to 24	$3^{1/8}$ x $3^{1/8}$ to $4^{3/4}$ x $4^{3/4}$ to $9^{1/2}$
Units/Surface	54,80 /m²	5,1 /ft²
Qty/row	0,91 m²	9,8 ft²
Qty/cube	8,20 m²	88,4 ft²
Weight/cube	1525 kg	3355 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	2,27 m²	24,4 ft²

COLOURS

Limestone grey
Garnet red
Sandstone beige
Terracotta brown

Shaded colours available on request



	HEIGHT X WIDTH X LENGTH CM / IN	
Module 2	8 x 16 to 22 x 16 to 28	$3^{1/8}$ x $6^{1/4}$ to $8^{5/8}$ x $6^{1/4}$ to 11
Units/Surface	25,20 /m²	2,3 /ft²
Qty/row	0,91 m²	9,8 ft²
Qty/cube	8,20 m²	88,4 ft²
Weight/cube	1525 kg	3355 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg)	3,78 m²	40,7 ft²

Product on special order for minimum quantity.

COLOURS



Limestone grey



Sandstone beige




Terracotta brown




Garnet red


PATTERNS




Modular runner pattern



Modular runner pattern



Runner pattern



Runner pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

VIA APPIA® 80 PAVER

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Via Appia 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m² (0,74 oz / ft²) after 28 cycles 500 g/m² (1,64 oz / ft²) after 49 cycles	5 % maximum	Lenght: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in Part 2 - Products of section 32 14 13 - Precast Concrete Pavers. It prescribes the choice of BOLDUC pavers and slabs for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, colour and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

.1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.

.2 Via Appia 80 paver supplied by BOLDUC.

.1 Thickness: 8 cm (3 1/8 in)

.2 Nominal Dimensions:

.3 Colour :

.4 Texture :

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.