

CITADIN® M80 PERMEABLE PAVER

REGULAR FINISH



CITADIN® M80 PERMEABLE PAVER


	HEIGHT/WIDTH/LENGTH	
	DIMENSIONS (CM)	DIMENSIONS (IN)
	8 x 16,3 x 32,5	3 ^{1/8} x 6 ^{3/8} x 12 ^{13/16}
	Joint 8mm Ouverture surface 7,26%	
Units/Surface	18,93 / m ²	1,76 / ft ²
Qty/row	1,11 m ²	11,94 ft ²
Qty/cube	8,88 m ²	95,52 ft ² 8 rows
Weight/unit avg.	10 kg	22 lb
Weight/cube	1643 kg	3622 lb

SPECIFICATIONS	CODES	COLORS
Regular finish	PPC-419R-02	Ice gray
	PPC-419R-15	Gray and charcoal

COLORS




● Ice gray



● Gray and charcoal

PATTERN



Runner pattern

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Citadin M80 permeable paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)