

# ACADIA® M70 PAVER



## ACADIA® M70 PAVER



	HEIGHT/WIDTH/LENGTH		
	DIMENSIONS (CM)	DIMENSIONS (IN)	
A	7 x 10 x 20	2 <sup>3/4</sup> x 3 <sup>15/16</sup> x 7 <sup>7/8</sup>	
B	7 x 20 x 20	2 <sup>3/4</sup> x 7 <sup>7/8</sup> x 7 <sup>7/8</sup>	
C	7 x 20 x 30	2 <sup>3/4</sup> x 7 <sup>7/8</sup> x 11 <sup>13/16</sup>	
Units/Surface	25 / m <sup>2</sup>	2,32 / ft <sup>2</sup>	
Qty/row	1,08 m <sup>2</sup>	11,63 ft <sup>2</sup>	
Qty/cube	9,72 m <sup>2</sup>	104,63 ft <sup>2</sup>	9 rows
Weight/unit avg.	6,7 kg	14,7 lb	
Weight/cube	1645 kg	3620 lb	

SPECIFICATIONS	CODES	COLORS
	PPC-101P-15	Gray and charcoal
	PPC-101P-24	Travertine beige


Sold together

Approximate coverage areas for one bag of polymeric sand ( 22,7 kg ) 4,50 m<sup>2</sup>    48,4 ft<sup>2</sup>

## COLORS




● Gray and charcoal




● Travertine beige

## PATTERNS



Pattern 1  
Runner pattern



Pattern 2  
Modular pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

## TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Resistance to freeze-thaw cycles in a saline solution	Water absorption	Dimensional tolerances
Acadia M70 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in a saline solution (NaCl 3 %): 225 g/m <sup>2</sup> (0,74 oz / ft <sup>2</sup> ) after 28 cycles 500 g/m <sup>2</sup> (1,64 oz / ft <sup>2</sup> ) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.