


HEXAGON™ 80 PAVER

PREMIUM FINISH ⓘ



HEXAGON™ 80 PAVER

	HEIGHT X WIDTH X LENGTH CM / IN	
	8 x 20 x 23	3 ¹ / ₈ x 7 ⁷ / ₈ x 9 ¹ / ₈
Units/Surface	28,57 /m ²	2,7 / ft ²
Qty/row	0,97 m ²	10,44 ft ²
Qty/cube	9,7 m ²	104,4 ft ² 10 rows
Weight/unit	6,3 kg	13,86 lb
Weight/cube	1792 kg	3943 lb



COLORS

- Granite gray ⓘ
- Black
- Avenue
- Certain colors in the Avenue series contribute to the LEED program. ⓘ

FINISH

- Grenart Premium ⓘ
- Smooth Premium ⓘ
- Avenue
- Certain finishes in the Avenue series contribute to the LEED program. ⓘ

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 5,77 m² 62,1 ft²

COLORS



● Granite gray ⓘ ● Black

AVENUE SERIES COLORS




Avenue Series colors and finishes are available upon request, minimum quantity required.



Colors contributing to LEED program solar reflective indices can help reduce the heat island effect in urban settings.

PATTERN



The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

HEXAGON™ 80 PAVER

PREMIUM FINISH

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Hexagon 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC autoblocking Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, color and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

1. Precast concrete pavers complying with CSA A231.2 and the following prescriptions.
2. Hexagon 80 paver supplied by BOLDUC.
 1. Thickness: 8 cm (3¹/₈ in)
 2. Nominal Dimensions: 8 x 20 x 23 cm (31/8 x 77/8 x 91/8 in)
 3. Color :
 4. Texture (Regular or Smooth Premium finish or Regular or Grenart premium finish):

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.