

AVENUE® 150 SL

REGULAR OR PREMIUM FINISHES



AVENUE M150 SL

	HEIGHT X WIDTH X LENGTH CM / IN	
	15 x 32 x 24	5 ^{7/8} x 12 ^{5/8} x 9 ^{7/16}
	15 x 32 x 32	5 ^{7/8} x 12 ^{5/8} x 12 ^{5/8}
	15 x 32 x 36	5 ^{7/8} x 12 ^{5/8} x 14 ^{3/16}
	15 x 32 x 40	5 ^{7/8} x 12 ^{5/8} x 15 ^{3/4}
	15 x 32 x 44	5 ^{7/8} x 12 ^{5/8} x 17 ^{5/16}
Units/Surface	8,68 /m ²	0,81 /ft ²
Qty/row	1,15 m ²	12,4 ft ²
Qty/cube	4,60 m ²	49,60 ft ²
Weight/cube	1665 kg	3671 lb



COLORS	
	Granite gray
	Light gray
	Silver gray
	Smoke gray
	Anthracite
	Opal white
	Ivory
	Light beige
	Sahara beige
	Burned beige
	Sandhill beige
	Salmon
	Clay red
	Red
	Burgundy
	Caledonia pink
	Brown
	Bistre



Approximate coverage areas for one bag of polymeric sand (22,7 kg) 3,75 m² 40,4 ft²




AVENUE 150 SL - 200 X 200

	HEIGHT X WIDTH X LENGTH CM / IN	
	15 x 20 x 20	5 ^{7/8} x 7 ^{7/8} x 7 ^{7/8}
Units/Surface	25 /m ²	2,32 /ft ²
Qty/row	0,96 m ²	10,33 ft ²
Qty/cube	3,84 m ²	41,33 ft ²
Weight/cube	1392 kg	3069 lb



FINISHES	
	Smooth Regular
	Granart Regular
	Smooth Premium 
	Granart Premium 

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 1,78 m² 19,2 ft²



AVENUE 150 SL - 300 X 600

	HEIGHT X WIDTH X LENGTH CM / IN	
	15 x 30 x 60	5 ^{7/8} x 11 ^{13/16} x 23 ^{5/8}
Units/Surface	5,6 /m ²	0,52 /ft ²
Qty/row	1,08 m ²	11,63 ft ²
Qty/cube	4,32 m ²	46,52 ft ²
Weight/cube	1563 kg	3446 lb



Approximate coverage areas for one bag of polymeric sand (22,7 kg) 3,54 m² 38,1 ft²

COLORS




Colors with solar reflectance indices contributing to the LEED program in order to reduce the creation of heat islands in urban areas as much as possible.


AVENUE® 150 SL

REGULAR OR PREMIUM FINISHES


PATTERNS




Modular pattern -
Avenue M150 SL



Checker pattern -
Avenue 150 SL - 200 - 200



Checker pattern -
Avenue 150 SL - 300 - 600



Runner pattern -
Avenue 150 SL - 300 - 600

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Avenue 150 SL paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC autoblocking Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, color and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

1. Precast concrete pavers complying with CSA A231.2 and the following prescriptions.
2. Avenue 150 SL paver supplied by BOLDUC.
 1. Thickness: 15 cm (5^{7/8} in)
 2. Nominal Dimensions:
 3. Color:
 4. Texture (Regular or Smooth Premium finish or Regular or Grenart premium finish):

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.