


PRESTIGE™ 60 PAVER



PREMIUM FINISHES





PRESTIGE™ 60 PAVER

	HEIGHT X WIDTH X LENGTH CM / IN	
	6 x 10 x 20	2 ^{3/8} x 3 ^{15/16} x 7 ^{7/8}
Units/Surface	50 /m ²	4,7 /ft ²
Qty/cube	10,56 m ²	113,7 ft ²
Weight/cube	1591 kg	3508 lb

Approximate coverage areas for one bag of polymeric sand (22,7 kg) 4,56 m² 49,1 ft²

COLORS	
	Granite gray 
	Anthracite

FINISHES	
	Grenart Premium 
	Smooth Premium 

Avenue Series colors and finishes are available upon request.

	HEIGHT X WIDTH X LENGTH CM / IN	
	6 x 20 x 20	2 ^{3/8} x 7 ^{7/8} x 7 ^{7/8}
Units/Surface	25 /m ²	2,3 /ft ²
Qty/cube	10,56 m ²	113,7 ft ²
Weight/cube	1591 kg	3508 lb


Approximate coverage areas for one bag of polymeric sand (22,7 kg) 6,82 m² 73,4 ft²


One size per cube

COLORS

GRENART FINISH





● Granite gray 




● Anthracite

SMOOTH FINISH



● Granite gray 




● Anthracite




Colors contributing to LEED program solar reflective indices can help reduce the heat island effect in urban settings.

PATTERNS



Checker pattern



Runner pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

PRESTIGE™ 60 PAVER

PREMIUM FINISHES

TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Prestige 60 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m ² (0,74 oz / ft ²) after 28 cycles 500 g/m ² (1,64 oz / ft ²) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC autoblocking Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, color and finish.

PART 2 - PRODUCTS

2.1 Precast Concrete Pavers

- 1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.
- 2 Prestige 60 paver supplied by BOLDUC.
 - 1 Thickness: 6 cm (2^{3/8} in)
 - 2 Nominal Dimensions:
 - 3 Color :
 - 4 Texture : Smooth Premium or Grenart Premium finishes

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.