

# PRESTIGE™ 80 PAVER

## PREMIUM FINISHES







### PRESTIGE™ 80 PAVER



	HEIGHT X WIDTH X LENGTH CM / IN	
	8 x 20 x 40	3 <sup>1</sup> / <sub>8</sub> x 7 <sup>7</sup> / <sub>8</sub> x 15 <sup>3</sup> / <sub>4</sub>
Units/Surface	12,5 /m <sup>2</sup>	1,16 /ft <sup>2</sup>
Qty/row	0,96 m <sup>2</sup>	10,33 ft <sup>2</sup>
Qty/cube	8,64 m <sup>2</sup>	92,97 ft <sup>2</sup>
Weight/unit	15 kg	33 lb
Weight/cube	1599 kg	3525 lb

Approximate coverage areas for one bag of polymeric sand ( 22,7 kg ) 7,37 m<sup>2</sup>    79,3 ft<sup>2</sup>

COLORS	
	Granite gray 
	Anthracite

FINIS	
	Grenart Premium 
	Smooth Premium 

Avenue Series colors and finishes are available upon request.



	HEIGHT X WIDTH X LENGTH CM / IN	
	8 x 40 x 40	3 <sup>1</sup> / <sub>8</sub> x 15 <sup>3</sup> / <sub>4</sub> x 15 <sup>3</sup> / <sub>4</sub>
Units/Surface	6,25 /m <sup>2</sup>	0,58 /ft <sup>2</sup>
Qty/row	0,96 m <sup>2</sup>	10,33 ft <sup>2</sup>
Qty/cube	8,64 m <sup>2</sup>	92,97 ft <sup>2</sup>
Weight/unit	30 kg	66 lb
Weight/cube	1599 kg	3525 lb

Approximate coverage areas for one bag of polymeric sand ( 22,7 kg ) 11,04 m<sup>2</sup>    118,8 ft<sup>2</sup>




	HEIGHT X WIDTH X LENGTH CM / IN	
	8 x 40 x 60	3 <sup>1</sup> / <sub>8</sub> x 15 <sup>3</sup> / <sub>4</sub> x 23 <sup>5</sup> / <sub>8</sub>
Units/Surface	4,17 /m <sup>2</sup>	0,39 /ft <sup>2</sup>
Qty/row	0,96 m <sup>2</sup>	10,33 ft <sup>2</sup>
Qty/cube	8,64 m <sup>2</sup>	92,97 ft <sup>2</sup>
Weight/unit	45 kg	99 lb
Weight/cube	1599 kg	3525 lb


Approximate coverage areas for one bag of polymeric sand ( 22,7 kg ) 13,24 m<sup>2</sup>    142,5 ft<sup>2</sup>

## COLORS

### GRENART FINISH





● Granite gray 




● Anthracite

### SMOOTH FINISH



● Granite gray 




● Anthracite




Colors contributing to LEED program solar reflective indices can help reduce the heat island effect in urban settings.


## PATTERNS




Checker pattern




Ranner pattern




Ranner pattern



Ranner pattern



Ranner pattern



Modular pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

# PRESTIGE™ 80 PAVER

## PREMIUM FINISHES

### TECHNICAL INFORMATION

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Prestige 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m <sup>2</sup> (0,74 oz / ft <sup>2</sup> ) after 28 cycles 500 g/m <sup>2</sup> (1,64 oz / ft <sup>2</sup> ) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

### SPECIFICATION CLAUSE

**SPEC. NOTE:** Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC autoblocking Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, color and finish.

#### PART 2 - PRODUCTS

##### 2.1 Precast Concrete Pavers

- 1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.
- 2 Prestige 80 paver supplied by BOLDUC.
  - 1 Thickness: 8 cm (3<sup>18</sup> in)
  - 2 Nominal Dimensions:
  - 3 Color :
  - 4 Texture : Smooth Premium or Grenart Premium finishes

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.