

# CLASSIC<sup>MC</sup> 80 PAVER



## CLASSIC<sup>MC</sup> 80 PAVER



	HEIGHT X WIDTH X LENGTH CM / IN		
	8 x 10,8 x 21,6	3 <sup>1/8</sup> x 4 <sup>1/4</sup> x 8 <sup>1/2</sup>	
Units/Surface	43,52 /m <sup>2</sup>	4,0 /ft <sup>2</sup>	Gray
Qty/cube	9,33 m <sup>3</sup>	100,4 ft <sup>3</sup>	Black
Weight/cube	1728 kg	3802 lb	

Approximate coverage areas for one bag of polymeric sand ( 22,7 kg ) 4,00 m<sup>2</sup> 43,0 ft<sup>2</sup>

COLORS  
Gray  
Black

Avenue Series colors and finishes are available upon request.



	HEIGHT X WIDTH X LENGTH CM / IN		
	8 x 25 x 25	3 <sup>1/8</sup> x 9 <sup>13/16</sup> x 9 <sup>13/16</sup>	
Units/Surface	16 /m <sup>2</sup>	1,5 /ft <sup>2</sup>	
Qty/cube	8,46 m <sup>3</sup>	91,08 ft <sup>3</sup>	
Weight/cube	1568 kg	3457 lb	

Approximate coverage areas for one bag of polymeric sand ( 22,7 kg ) 6,00 m<sup>2</sup> 64,6 ft<sup>2</sup>

## COLORS




● Gray




● Black


## PATTERNS




Herringbone pattern




Checker pattern




Checker pattern 45°



Runner pattern



Runner pattern



Basket weave pattern

The layout shown in the above illustration is for information purposes only. Bolduc disclaims all responsibility for the excess or lack of pavers resulting from an installation according to these laying patterns.

## TECHNICAL INFORMATIONS

Product	Standard	Compressive strength	Durability to freeze-thaw cycles with utilisation of de-icing salts	Water absorption	Dimensional tolerances
Classic 80 paver	CSA A231.2	50 MPa (7250 psi)	Maximum loss of initial weight in saline solution (NaCl 3%): 225 g/m <sup>2</sup> (0,74 oz / ft <sup>2</sup> ) after 28 cycles 500 g/m <sup>2</sup> (1,64 oz / ft <sup>2</sup> ) after 49 cycles	5 % maximum	Length: -1 mm to +2 mm (-1/32 in to + 5/64 in) Width: -1 mm to +2 mm (-1/32 in to + 5/64 in) Height: ±3 mm (±1/8 in)

## SPECIFICATION CLAUSE

**SPEC. NOTE:** Include the following article in part 2-Products of section 32 14 13-Precast Concrete Pavers. It prescribes the choice for BOLDUC autoblocking Urban Pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, color and finish.

### PART 2 - PRODUCTS

#### 2.1 Precast Concrete Pavers

1. Precast concrete pavers complying with CSA A231.2 and the following prescriptions.
2. Classic 80 paver supplied by BOLDUC.
  1. Thickness: 8 cm (3<sup>1/8</sup> in)
  2. Nominal Dimensions:
  3. Color:
  4. Texture (Regular or Grenart finishes):

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.